

Share:



Back-UPS 300

BK300C



Be the first to [write a review](#)

Description: Battery Backup & Surge Protector for Electronics and Computers



Product Overview

Technical Specifications

Documentation

Ratings & Reviews

Output

[Print Technical Specification](#)

Output power capacity	180Watts / 300VA
Max Configurable Power (Watts)	180Watts / 300VA
Nominal Output Voltage	120V
Topology	Standby
Output Connections	(2) NEMA 5-15R (Battery Backup)
Transfer Time	4ms typical : 8ms maximum

Input

Nominal Input Voltage	120V
Input frequency	60 Hz +/- 3 Hz
Input Connections	NEMA 5-15P
Cord Length	6ft (1.83meters)
Input voltage range for main operations	103 -150V
Input voltage adjustable range for mains operation	88 -150V
Number of Power Cords	1

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	6hour(s)
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Volt-Amp-Hour Capacity	71

Communications & Management

Interface Port(s)	DB-9 RS-232
Control panel	Output power on indicator LED
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rating	320Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Physical	
Maximum Height	6.0inches (152mm , 15.2cm)
Maximum Width	3.4inches (86mm , 8.6cm)
Maximum Depth	13.1inches (333mm , 33.3cm)
Maximum Weight	42.0lbs (19.0kg)



Shipping Width	7.6inches (193mm , 19.3cm)
Shipping Depth	16.5inches (419mm , 41.9cm)
Color	Beige
Master Carton Units	2.0
Units per Pallet	60.0
SCC Codes	1073130400981; 00981 5

Environmental

Operating Environment	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000ft (0-15000meters)
Audible noise at 1 meter from surface of unit	40.0dBA
Online thermal dissipation	10.0BTU/hr

Conformance

Approvals	CSA, UL 1778
Equipment protection policy	Lifetime : \$25000
Standard warranty	2 years repair or replace

Life Is On | Schneider Electric

Sign up to stay up to date with best practices, new solutions and special offers.

Email

OK

WHO WE ARE >

CONNECT WITH US >

FIND A RESELLER

Zip/Postal Code

FIND



CATALOG KEYCODE

Enter Key Code

GO





[TERMS & CONDITIONS](#) >

[PRIVACY STATEMENT](#) >

