

Share:



APC BACK-UPS ES 8 OUTLET 350VA 120V

BE350R

Average Customer Review  5 

1 of 1 (100%) reviewers would recommend this product to a friend.

[Read all reviews](#) | [Write a review](#)

Product Overview

Technical Specifications

Documentation

Software & Firmware

Ratings & Reviews

Output

[Print Technical Specification](#) 

Output power capacity	200Watts / 350VA
Max Configurable Power (Watts)	200Watts / 350VA
Nominal Output Voltage	120V
Topology	Standby
Waveform type	Stepped approximation to a sine wave
Output Connections	(4) NEMA 5-15R (selector_surgetitle) (4) NEMA 5-15R (Battery Backup)

Input

Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	6ft (1.83meters)
Input voltage range for main operations	88 - 139V
Number of Power Cords	1

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	
Typical recharge time	16hour(s)	
Expected Battery Life (years)	3 - 5	
RBC Quantity	1	
Battery Volt-Amp-Hour Capacity	29	
Runtime	View Runtime Graph	View Runtime Chart
Efficiency	View Efficiency Graph	

Communications & Management

Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	365Joules
Data Line Protection	RJ-11 Modem/Fax/DSL protection (two wire single line)
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	3.39inches (86mm . 8.6cm)
----------------	-----------------------------



Net Weight	9.47lbs. (4.3kg)
Shipping weight	10.57lbs. (4.8kg)
Shipping Height	4.69inches (119mm , 11.9cm)
Shipping Width	15.0inches (381mm , 38.1cm)
Shipping Depth	8.9inches (226mm , 22.6cm)
Color	Charcoal
Master Carton Units	2.0
Master Carton Weight	22.05lbs. (0.0)
Units per Pallet	100.0
SCC Codes	1073130422735 6

Environmental

Operating Environment	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-50000ft (0-15000meters)
Audible noise at 1 meter from surface of unit	45.0dBA
Online thermal dissipation	14.0BTU/hr

Conformance

Approvals	cUL Listed, FCC Part 15 Class B, FCC Part 68, NOM, UL 1778, UL 497A, UL 498
Equipment protection policy	Lifetime : \$75000
Standard warranty	3 years repair or replace

Sustainable Offer Status

PEP	Available in Documentation tab
EOLI	Available in Documentation tab



Sign up to stay up to date with best practices, new solutions and special offers.

Email

OK

CONNECT WITH US >

FIND A RESELLER

Zip/Postal Code

FIND



CATALOG KEYCODE

Enter Key Code

GO



TERMS & CONDITIONS >

PRIVACY STATEMENT >

© 2016, APC by Schneider Electric