

Share:



APC Back-UPS ES 8 Outlet 550VA 120V

BE550R

Average Customer Review  2 

0 of 2 (0%) reviewers would recommend this product to a friend.

[Read all reviews](#) | [Write a review](#)

Description: Best Value UPS with Battery Backup & Surge Protection for Home Computers

Includes : CD with software , Free Trial Software , USB cable , User Manual , Wall-mounting template



Product Overview

Technical Specifications

Documentation

Software & Firmware

Ratings & Reviews

Output

[Print Technical Specification](#) 

Output power capacity	330Watts / 550VA
Max Configurable Power (Watts)	330Watts / 550VA
Nominal Output Voltage	120V
Output Frequency (sync to mains)	60 Hz
Output Frequency (not synced)	60Hz +/- 0.1% for 60Hz nominal
Topology	Standby
Waveform type	Stepped approximation to a sinewave
Output Connections	(4) NEMA 5-15R (Battery Backup) (4) NEMA 5-15R (selector_surgetitle)

Input

Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	6ft (1.83meters)
Input voltage range for main operations	88 - 139V
Number of Power Cords	1

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	
Typical recharge time	24hour(s)	
Expected Battery Life (years)	3 - 5	
RBC Quantity	1	
Battery Volt-Amp-Hour Capacity	84	
Runtime	View Runtime Graph	View Runtime Chart
Efficiency	View Efficiency Graph	

Communications & Management

Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault

Audible Alarm

Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating

365Joules

Data Line Protection

RJ-11 Modem/Fax/DSL protection (two wire single line)

Filtering

Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height

3.4inches (86mm , 8.6cm)

Maximum Width

10.9inches (277mm , 27.7cm)

Maximum Depth

7.1inches (180mm , 18.0cm)



Shipping Height

9.1inches (231mm , 23.1cm)

Shipping Width

15.0inches (381mm , 38.1cm)

Shipping Depth

8.9inches (226mm , 22.6cm)

Color

Charcoal

Master Carton Units

2.0

Master Carton Weight

29.0lbs. (13.18)

Units per Pallet

120.0

SCC Codes

1 073130424806 1

Environmental

Operating Environment

32 - 104 °F (0 - 40 °C)

Operating Relative Humidity

5 - 95 %

Operating Elevation

0-10000ft (0-3000meters)

Storage Temperature

-15 - 45 °C

Storage Relative Humidity

5 - 95 %

Storage Elevation

0-50000ft (0-15000meters)

Audible noise at 1 meter from surface of unit

45.0dBA

Online thermal dissipation

16.0BTU/hr

Conformance

Approvals

cUL Listed, FCC Part 15 Class B, FCC Part 68, NOM, UL 1778, UL 497A, UL 497B

Equipment protection policy

Lifetime : \$75000

Standard warranty

3 years repair or replace

Sustainable Offer Status

PEP

Available in Documentation tab

EOLI

Available in Documentation tab



Sign up to stay up to date with best practices, new solutions and special offers.

Email

OK

WHO WE ARE >

CONNECT WITH US >

FIND A RESELLER

Zip/Postal Code

FIND



CATALOG KEYCODE

Enter Key Code

GO



TERMS & CONDITIONS >

PRIVACY STATEMENT >

© 2016, APC by Schneider Electric