

Share:



Back-UPS XS 1500VA RETAIL

BX1500



Be the first to [write a review](#)

Includes : CD with software , Cord Management Straps , Free trial of anti-virus : firewall : email privacy : system recovery and online backup software , USB cable , User Manual



Output

[Print Technical Specification](#)

Output power capacity	865Watts / 1.5 kVA
Max Configurable Power (Watts)	865Watts / 1.5 kVA
Nominal Output Voltage	120V
Topology	Line Interactive
Maximum Output Current	12
Output Connections	(6) NEMA 5-15R (Battery Backup) (2) NEMA 5-15R (selector_surgetitle)

Input

Nominal Input Voltage	120V
Input frequency	47 - 63 Hz
Input Connections	NEMA 5-15P
Cord Length	6ft (1.83meters)
Input voltage range for main operations	88 - 148V
Input voltage adjustable range for mains operation	78 - 152V
Number of Power Cords	1

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	
Included Battery Modules	1	
Typical recharge time	6hour(s)	
Expected Battery Life (years)	4 - 6	
RBC Quantity	1	
Battery Volt-Amp-Hour Capacity	186	
Runtime	View Runtime Graph	View Runtime Chart

Communications & Management

Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators

Audible Alarm

Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rating

420Joules

Data Line Protection

RJ-11 Modem/Fax/DSL protection (two wire single line)

Filtering

Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height

14.6inches (371mm , 37.1cm)

Maximum Width

3.4inches (86mm , 8.6cm)

Maximum Depth

13.1inches (333mm , 33.3cm)

Rack Height

2U

Net Weight

25.0lbs. (11.36kg)

Shipping weight

26.0lbs. (11.82kg)

Shipping Height

17.9inches (455mm , 45.5cm)



Color

Beige

Master Carton Units

1.0

Units per Pallet

30.0

Environmental

Operating Environment

32 - 104 °F (0 - 40 °C)

Operating Relative Humidity

0 - 95 %

Operating Elevation

0-10000ft (0-3000meters)

Storage Temperature

-5 - 45 °C

Storage Relative Humidity

0 - 95 %

Storage Elevation

0-50000ft (0-15000meters)

Audible noise at 1 meter from surface of unit

45.0dBA

Online thermal dissipation

180.0BTU/hr

Conformance

Approvals

cUL Listed, FCC Part 15 Class B, FCC Part 68, UL 1449, UL 1778, UL Listed

Equipment protection policy

Lifetime : \$150000

Standard warranty

2 years repair or replace



Sign up to stay up to date with best practices, new solutions and special offers.

Email

OK

WHO WE ARE >

CONNECT WITH US >

FIND A RESELLER

Zip/Postal Code

FIND



CATALOG KEYCODE

Enter Key Code

GO



[TERMS & CONDITIONS](#) >

[PRIVACY STATEMENT](#) >

© 2016, APC by Schneider Electric

