

Product data sheet

Specifications



Rack PDU, Metered, Zero U, 30A, 200/208V, (20)C13 & (4)C19

AP7841

! Discontinued on: 23 August 2021

! End-of-service on: 14 June 2022

! Discontinued

Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

Main

Main Input Voltage	200 V 208 V 230 V
PDU Type	Metered
Main Output Voltage	200 V 208 V 230 V 240 V
Input Connection Type	NEMA L6-30P
Number of rack unit	0U
Cable length	10 ft (3.05 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Toolless Mounting Kit

Physical

Color	Black
Height	63.74 in (161.9 cm)
Width	2.20 in (5.6 cm)
Depth	1.73 in (4.4 cm)
Net Weight	12.52 lb(US) (5.68 kg)
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Vertical

Input

Line Rated Current	24 A
Permissible voltage	200...240 V
Input current limits	30 A

Load Capacity	4992 VA
Input Frequency	50/60 Hz
Output	
Number of power socket outlets	20 IEC 60320 C13 4 IEC 60320 C19
Conformance	
Product Certifications	cUL Listed Industry Canada METI Denan PSE UL Listed VCCI Class A VCCI
Standards	CSA C22.2 No. 60950-1-03 FCC Part 15 class A ICES-003 UL 60950-1
Environmental	
Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Ordering and shipping details	
GTIN	731304225546
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.02 in (213.4 cm)
Package 1 Width	5.98 in (15.2 cm)
Package 1 Length	5.00 in (12.7 cm)
Package 1 Weight	14.52 lb(US) (6.586 kg)
Offer Sustainability	
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)

AP7841 is replaced by:

1x		APC Rack PDU, 2G, metered, 0U, 30A, 200V and 208V, 36 C13 and 6 C19 sockets AP8841
----	---	---