

Product data sheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 17.3kW, 208V, (20) C13/C15, (12) C19/C21

APDU9966

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	208 V 3 phase
PDU Type	Switched
Main Output Voltage	208 V
Input Connection Type	IEC 60309 60 A 3P+PE
Cable length	6 ft (1.83 m)
Number of cables	1
Communication Port Protocol	SNMP Redfish
Provided Equipment	Installation guide Rack Mounting brackets Safety guide

Batteries & Runtime

Communication Network Type	10/100/1000BASE-T
----------------------------	-------------------

Physical

Color	Black
Height	72.17 in (183.3 cm)
Width	4.37 in (11.1 cm)
Depth	2.99 in (7.6 cm)
Net Weight	30.86 lb(US) (14 kg)
Mounting Location	Side
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Line Rated Current	48 A
Max line current	48 A
Input current limits	60 A

Load Capacity	17300 VA
Input Frequency	50/60 Hz
Output	
Number of power socket outlets	20C13/C15 12C19/C21
Conformance	
Product Certifications	cUL Listed FCC part 15 class A
Standards	IEC 62368-1
Environmental	
Ambient air temperature for operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Ordering and shipping details	
GTIN	731304356332
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.61 in (214.9 cm)
Package 1 Width	4.41 in (11.2 cm)
Package 1 Length	8.70 in (22.1 cm)
Package 1 Weight	44.00 lb(US) (19.96 kg)
Offer Sustainability	
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Warranty	3 years repair or replace
Recommended replacement(s)	