

Product data sheet

Specifications



Rack PDU, Metered, Zero U, 5.7kW, 208V, (36)C13 & (6)C19

AP7864

 **Discontinued on:** Jun 14, 2022

 **Discontinued**

Overview

Lead time While Supplies Last

Main

Color	Black
Product or Component Type	PDU
PDU Type	Metered
Cord length	3 ft (0.9 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Toolless Mounting Kit User Manual

Complementary

Input Voltage	208 V 3 phase
Height	70.00 in (177.8 cm)
Width	2.20 in (5.6 cm)
Output Voltage	208 V
Depth	1.73 in (4.4 cm)
Net Weight	12.02 lb(US) (5.45 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA L21-20P
Mounting Mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Line Rated Current	16 A
Input current limits	20 A
Load Capacity	5700 VA
Number of power socket outlets	42
Input Frequency	50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Outlet type and quantity	36 IEC 60320 C13 6 IEC 60320 C19
--------------------------	-------------------------------------

Environment

Product Certifications	cUL Listed Industry Canada METI Denan UL Listed VCCI
Standards	CSA C22.2 No. 60950-1-03 FCC Part 15 class A ICES-003 UL 60950-1
Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0...15240 m)

Ordering and shipping details

GTIN	731304214328
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	84.02 in (213.4 cm)
Package 1 Width	5.98 in (15.2 cm)
Package 1 Length	5.00 in (12.7 cm)
Package weight(Lbs)	19.491 lb(US) (8.841 kg)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile
Use Better	
Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
Use Again	
Repack and remanufacture	
Circularity Profile	End of Life Information

Image of product / Alternate images

Alternative

